Lanier Worldwide, Inc.
2300 Parklake Dr., N. E.
Atlanta, GA 30345-2979
Emergency Telephone: (800) 526-4371

MATERIAL SAFETY DATA SHEET

Section 1: Chemical Product and Company Information

Identity:	**Toner for 5025**	MSDS No.	**CP- 306C**
Product ID:	480-0015	Issued:	9/29/99
		Supersedes:	**None**
Synonyms		**Date:**	**9/29/99**
& Common	Toner for	**Prepared by:**	**Lanier QA/EH&S Department 770-493-2361**
Names:	Lanier 5025	**Approved by:**	Larry Choskey, Sr. Quality Assurance Engineer
		European Contact:	**Lanier Worldwide**, WSM Europe,
Uses:	Lanier 5025		Walter Fricke,
			Im Taubental D-41468 Neuss, Germany
Chemical			+49-2131-387-177
Formula:	Mixture		

Section 2: Composition / Information on Ingredients

	PERCENT	CAS No.	EXPOSURE LIMITS	SOURCE
Polyester resin	68.0	Confidential	Not listed	n/a
Styrene acrylic polymer	17.0	26655-10-7	Not listed	n/a
Carbon black	8.0	1333-86-4	3.5mg/m^3 3.5mg/m^3	OSHA PEL ACGIH TWA
Wax	4.0	8015-86-9	Not listed	N/a
Dye	2.0	31714-55-3	Not listed	n/a
Silica	1.0	172640-49-2	Not listed	N/a

*PEL as the product: 15mg/m^3 (total dust), 5mg/m^3 (respirable dust)
*TLV as the product: 10mg/m^3 (total dust), 5mg/m^3 (respirable dust)

Section 3: Hazards Identification

HMIS Rating:
FLAMMABILITY = 1 HEALTH = 1
REACTIVITY = 0 SPECIAL = none

Health Hazards (Acute, Chronic, Immediate and Potential): Minimum irritation to respiratory tract may occur as with exposure to any non-toxic dust. May cause gasping if inhaled. Inhalation should be avoided. May cause temporary eye discomfort.
Health Hazards of Long Term exposure (Chronic): A manufacturer sponsored chronic inhalation study in rats using a special test toner revealed there were no lung changes at all in the lowest exposure level (1mg/m^3), the most relevant level to potential human exposures. A very slight degree of fibrosis was noted in 25% of the animals at the middle exposure level (4mg/m^3), while a slight degree of fibrosis was observed at the highest exposure level (16mg/m^3) in all animals. These findings are attributed to "Lung Overloading", a generic response to excessive amount of any dust retained in the lungs for a prolonged interval. The special test toner was ten times more respirable than commercially available toner to comply with EPA testing protocol and would not function properly in Xerographic equipment.
Carbon Black is listed on the IARC Monograph and the Massachusetts Substance List. The IARC has evaluated the evidence for the carcinogenicity of Carbon Black as inadequate to determine a carcinogenic risk for humans.
This product contains no known hazardous materials as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Section 4: First Aid Measures

Inhalation:	Remove to fresh air if effects occur. Get medical attention if needed.	**Eye Contact:**	In case of contact, immediately flush eyes with water for 5 minutes. Get medical attention if needed.
Skin Contact:	Wash with soap and water.	**Ingestion:**	Dilute stomach contents with several glasses of water. Get medical attention.

Section 5: Fire Fighting Measures

Suitable extinguishing media: CO_2, dry chemical, foam or water.
Extinguishing media which may not be used for safety reasons: none

This material will burn in case of fire. The decomposition products are CO, CO_2, and No_x. Avoid inhalation of smoke.
Special protective equipment for fire fighters: none
UEL: n/a LEL: n/a

Section 6: Accidental Release Measures

Spill / leak Procedures: If spilled, sweep up using an approved toner vacuum with a 0.5 micron filter or smaller, such as the Atrix AAA Toner Vacuum or 3M Toner Vacuum. Use of a vacuum cleaner not rated for toner particles, could result in a fire or personal injury. Remove residue with soap and cold water.
Miscellaneous: Keep product out of sewers and watercourses.

Personal protection: Avoid inhalation of dust.

Section 7: Handling and Storage

Special Handling: Cleanse skin after contact before breaks or meals, and end of workday.
Special Storage: Avoid direct sunlight. Keep out of reach of children. Store in a cool, dry place.

Section 8: Exposure Control and Personal Protection Information:

Respiratory Protection: none required under normal use.

Hand Protection: none required under normal use.

Eye Protection: none required under normal use.

Skin Protection: none required under normal use.

Section 9: Physical and Chemical Properties

CHARACTERISTICS:

Appearance:	Black	Melting point:	n/a
Form:	Powder	Vapor pressure:	n/a
Odor:	Slight plastic odor	Vapor density:	n/a
Solubility in Water:	Insoluble	Evaporation rate:	n/a
Bulk density:	~1.2	Boiling point:	n/a

Section 10: Stability and Reactivity

Conditions to avoid: none Materials to avoid: none Stability: Stable
Hazardous decomposition products: CO and CO2 and other decomposition products when burned.

Section 11: Toxicological Information:

Ames test negative

Section 12: Environmental / Ecological Information

None

Section 13: Disposal Consideration

Used Toner should be disposed of under conditions that meet all federal, state and local environmental regulations. Disposal regulations vary from locality to locality, therefore consult your local Lanier office or the EPA to determine the proper method for disposal. Do not incinerate loose or spilled Toner.

Section 14: Transportation Information

None. This is not a hazardous product.

Section 15: Regulatory Information

Canadian Disclosure List – Carbon Black (1333-86-4)

Section 16: Miscellaneous Information

Judgment as to the suitability of information contained herein for user's purposes is the responsibility of the purchaser. Therefore, although reasonable care has been taken in the preparation of this information, Lanier Worldwide, Inc. extends no warranties, makes no representations, and assumes no responsibility as to the accuracy or suitability of such information for application to user's intended purposes or for consequences of its use. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we do not guarantee that these are the only hazards that exist.